

OUTDOOR BARRIER NETTING MOUNTED ON ALUMINIUM POSTS

Art. no. 15 542

Made of alumunium profiles, square 80x80 mm, reinforced and ribbed. Profiles mounted in steel ground sockets. Height of profile after mounting in ground socket: 4,0 m; 5,0 m; 6,0 m. Profile has special channel for attaching net using PP hooks. Knotless net made of high strength polypropylene.

Mesh 12x12 cm, 10x10 cm, 4,5x4,5 cm. Strand thickness: 2,3 mm; 3,0 mm; 4,0 mm; 4,75 mm.

Colours: green, black, blue, white.

Certificate: DIN EN ISO 9001: 2000.







Profile has special channel for attaching net using PP hooks.

Net attached to the top and bottom part using steel line 3 mm thick, steel carabiners, galvanised.





Aluminium profiles, square 80x80 mm, reinforced, ribbed.





Knotless net made of high strength polypropylene. Mesh 12x12 cm, 10x10 cm, 4,5x4,5 cm.

Strand thickness: 2,3 mm; 3,0 mm; 4,0 mm; 4,75 mm.

Colours: green, black, blue, white. **Certificate: DIN EN ISO 9001 : 2000.**



Top part of the provile is covered, fitted with an eyelet for attaching steel line, which is tensioned using turnbuckle.

Aluminium profiles mounted in steel galvanized ground sockets, 0,7 m or 0,5 m long. Depends on barrier netting height.