

## BARRIER NETTING ON STEEL POSTS

ARTICLE NUMBER: 15 543

Made of steel profiles, square 80x80 mm, powder-coated in RAL 6024 or hot-dip galvanised.

Profiles fixed in steel sleeves.

Profile height after installation in the sleeve: 4.0 m; 5.0 m; 5.5 m; 6.0 m; 7.0 m or 8.0 m.

Knotless mesh made of high resistance polypropylene

Mesh: 12x12 cm; 10x10 cm; 4.5x4.5 cm.

Weave thickness: 2.3 mm; 3.0 mm; 4.0 mm; 4.75 mm.

Colour: green, black, blue, white.



Fixing the net in the lower and upper part to a 3 mm thick steel wire rope using galvanized steel snap hooks.



Knotless mesh made of high resistance polypropylene

Mesh: 12x12 cm; 10x10 cm; 4.5x4.5 cm.

Weave thickness: 2.3 mm; 3.0 mm; 4.0 mm; 4.75 mm.

Colour: green, black, blue, white.

**Certified acc. to DIN EN ISO 9001 : 2000.**

In the upper part of the profile is blanked, it has an eye for fixing the steel cord, which is tensioned by means of Roman screws.

Steel profiles fixed in galvanized steel sleeves, 0.7 m and 0.5 m long depending on the height of the ball-stop.

